

This 8W edgelite is specially designed for use in many prestigious applications. It is comprised of a gear tray with electrical components, white epoxy powder coated housing, legend panel, accessory kit, universal mounting box and brackets, RoHS compliant & CE mark

Specifications

Double sides version

Interior use only

Viewing distance: 40 m

Brass & chrome housing available

IP20

NF 8182501 - M / AD

NF 8182501 - M / AL

NF 8182501 - M / AR

NF 8182501 - NM / AD

NF 8182501 - NM / AL

NF 8182501 - NM / AR



Certificate	
Kitemark® Sub-Licence	
This is to certify that:	
Eurotech Fire Protection Limited 11 Lakeside Business Park Sandhurst Berkshire GU47 9DN	
In respect of:	
Emergency Luminaires	
Has the right to use the Kitemark under Sub-Licence from the Licensee, subject to the Kitemark Licence Conditions of Contract as may be updated from time to time by BSI. All defined terms in this certificate shall have the same meaning as in the Kitemark Licence Conditions of Contract.	
The right to use the Kitemark is in respect of the Product(s) provided from the address above and in conformity with the Standard(s) detailed on the following pages.	
For and on behalf of BSI:	
	
David W. Ford, Executive Director, Healthcare and Testing Services	
Date: 24 September 2010	Page 1 of 2
This is not a legal document	
raising standards worldwide™	
	

Certificate			
Kitemark® Sub-Licence			
Eurotech Fire Protection Limited 11 Lakeside Business Park Sandhurst Berkshire GU47 9DN			
BS EN 60598-1 & BS EN 60598-2-22 for Emergency Luminaires			
Product Information			
Model number	Voltage	Lamp	Lamp duration
NF8182301	230 - 240 V 50 / 60 HZ	T5 8 Watt	3 Hrs maintained
NF8182302	230 - 240 V 50 / 60 HZ	T5 8 Watt	3 Hrs non-maintained
Date: 24 September 2010			
Page 2 of 2			
This is not a legal document			
raising standards worldwide™			
			

