Alarm Valve

Model-H

Discription

Alarm Valve is a double seated clapper check valve with grooved seat design, which ensures positive water flow for alarm operation and is designed for installation in wet pipe sprinkler system. External bypass prevents with the provision of retard chamber, thus the design allows for installation under both variable and constant supply pressure

Operation of one or more automatic fire sprinklers causes the water to flow into the sprinklers system causing the alarm valve to open, allowing continuous flow of water into the system and transmittal of alarm, both electrical and mechanical.

Technical Data





MODEL Η

END CONNECTION Flange X Flange Flange X Groove Groove X Groove NOMINAL SIZE 200, 150, 100 & 80 NB

MAXIMUM SERIVCE **PRESSURE**

TRIM

BSPT THREADED OPENING **MOUNTING** Vertical

FLANGE CONNECTION ANSI B 16.42 # 150

(Flange drilling matching to ANSI B 16.5 # 150)

17.5 Bar (250 PSI)(*)

Galvanized fitting with Brass Valves.

35 Kg/sq.Cm. (500 PSI)

FACTORY HYDROSTATIC TEST PRESSURE

FRICTIONAL LOSS 200 NB - 7.50 Mtrs. IN TERMS OF 150 NB - 7 Mtrs. **EQUIVALENT LENGTH** 100 NB - 6.1 Mtrs. OF PIPE (C - 120) 80 NB - 4.7 Mtrs. **FINISH** Red RAL 3000

APPROVAL UL Listed & FM Approved. **ORDERING** Specify size of valve, Trim details, **INFORMATION** End connection & PIPE OD REFERENCE NFPA 13 and NFPA 25







Nitin Venture FZE. P.O. Box 262294, JAFZA

Dubai, UAE. Tel : +971 4 886 5858, Fax : +971 4 886 5859

Email: sales@nitinventures.com Web : www.nitinventures.com

NEW AGE COMPANY LLC

PO Box No. 7645, Abu Dhabi - UAE.

: +971 2 6774548 Fax : +971 2 6728880 Email: newage1@eim.ae Web: www.newage.ae



UAE HQ - Dubai Investment Park II, PO Box No. 4396, Dubai - UAE.

: +971 4 8868600, Fax : +971 4 8868999

Email: newage@eim.ae Web: www.newage.ae