



HLCV.EX16412 Strainers, Pipeline

[Page Bottom](#)

Strainers, Pipeline

[See General Information for Strainers, Pipeline](#)**NITIN VENTURES FZE**

EX16412

PO BOX 262294

JEBEL ALI

JAFZA

DUBAI, UNITED ARAB EMIRATES

Strainers, basket type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 200 psi, Model(s) NVFV70FF-200, NVFV70FG-200, NVFV70GG-200

Strainers, basket type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 250 psi, Model(s) NVFV70FF-250, NVFV70FG-250, NVFV70GG-250

Strainers, basket type, 2, 2.5, 3, 4, 5, 6, 8, 10 and 12 in. sizes, for rated working pressure of 300 psi, Model(s) NVFV70FF-300, NVFV70FG-300, NVFV70GG-300

NOTE - Loss of head will approximate 7.22 psi for the 2 in. size at 157.63 GPM, 5.89 psi for the 2-1/2 in. size at 224.86 GPM, 8.24 psi for the 3 in. size at 347.53 GPM, 5.88 psi for the 4 in. size at 598.54 GPM, 7.63 psi for the 5 in. size at 940.7 GPM, 4.82 psi for the 6 in. size at 1358.85 GPM, 5.83 psi for the 8 in. size at 2405.84 GPM, 7.25 psi for the 10 in. size at 3795.17 GPM and 5.73 psi for the 12 in. size at 5442.11 GPM.

[Last Updated](#) on 2016-04-15

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".